

Type	Wall Mounted /Heat pump /Single split		
Model	Indoor unit		FSAI-Pro-180AE1
	Outdoor unit		FSOAI-Pro-180AE1
Sound power level at standard rating cond. (indoor/outdoor)	[dB(A)]	55/65	
Refrigerant type		R410A	
Global Warming Potencial (GWP) *		1975	
SEER		5,6	
Energy efficiency class in cooling		A+	
Annual electricity consumption in cooling **	[KWh/a]	313	
Design load in cooling mode (P design)	[KW]	5	
SCOP (average season)		3,4	
Energy efficiency class in heating (average season)		A	
Annual electricity consumption in heating (average season) **	[KWh/a]	2100	
Design load in heating mode (P design)	[KW]	5,1	
Declared capacity at reference design condition (average season)	[KW]	3,8	
Back up heating capacity at reference design condition (average season)	[KW]	1,3	
Cooling Capacity at standard rating conditions***	[KW]	5	
Heating Capacity at standard rating conditions***	[KW]	5,27	
Power input at standard rating conditions*** cooling/heating	[KW]	1,78/1,5	
Dimension	Indoor unit	[mm]	930x198x275
	Outdoor unit	[mm]	760x285x590
Weight	Indoor unit	[kg]	9
	Outdoor unit	[kg]	35
Power source		230V~50Hz 1ph	

* Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to [1975]. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be [1975] times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

** The annual energy consumption kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

*** The standard rating conditions: cooling -outdoor 35°C DB/24°C WB -indoor 27°C DB/19°C WB
heating -outdoor 7°C DB/6°C WB -indoor 20°C DB/15°C WB

Operating Range:

	Indoor	Outdoor
Cooling mode	min. 17°C	0°C ~ 50°C
Dry mode	min. 10°C	0°C ~ 50°C
Heating mode	max. 30°C	-15°C ~ 30°C
Tha maximum humidity:	80%	-

If air conditioner is used outside of the above conditions, certain safety protection features may come into operation and cause the unit to function abnormally or damage.