

Type		Heat pump /Single split	
Model	Indoor unit		FSLIF-361AE2
	Outdoor unit		FSOIF-361AE2-3F
Sound power level at standard rating cond.		[dB(A)]	64/70
Refrigerant type			R410A
Global Warming Potencial (GWP) *			1975
SEER			5,10
Energy efficiency class in cooling			A
Annual electricity consumption in cooling **		[KWh/a]	721
Design load in cooling mode (P design)		[KW]	10,5
SCOP (average season)			3,80
Energy efficiency class in heating (average season)			A
Annual electricity consump.in heating (average season) **		[KWh/a]	3868
Design load in heating mode (P design)		[KW]	10,5
Declared capacity at reference design condition (average season)		[KW]	8,48
Back up heating capacity at reference design condition (average season)		[KW]	2,02
Cooling Capacity at standard rating conditions***		[KW]	10,5
Heating Capacity at standard rating conditions***		[KW]	11,7
Power input at standard rating conditions*** cooling/heating		[KW]	3,29/3,21
Dimension	Indoor unit	[mm]	1200x865x300
	Outdoor unit	[mm]	990X965X345
Weight	Indoor unit	[kg]	44
	Outdoor unit	[kg]	77
Power source			400V~50Hz 3ph

* Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to [1975]. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be [1975] times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

** The annual energy consumption kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

*** The standard rating conditions: cooling -outdoor 35°C DB/24°C WB -indoor 27°C DB/19°C WB
heating -outdoor 7°C DB/6°C WB -indoor 20°C DB/15°C WB

Operating Range:

	Indoor	Outdoor
Cooling mode	+17°C ~ +32°C	-15°C ~ +50°C
Dry mode	+17°C ~ +32°C	0°C ~ +50°C
Heating mode	0°C ~ +30°C	-15°C ~ + 24°C
The maximum humidity:	80%	-

If air conditioner is used outside of the above conditions, certain safety protection features may come into operation and cause the unit to function abnormally or damage.