

AIR CONDITIONER

PRODUCT FICHE

Туре		Wall Mount	Wall Mounted /Heat pump /Single split	
Model	Indoor unit		FSAIF-HT-181AE2	
woder	Outdoor unit		FSOAIF-HT-181AE2	
Sound power level at standard rating cond. (indoor/outdoor)		[dB(A)]	60/64	
Refrigerant type			R410A	
Global Warming Potencial (GWP) *			1975	
SEER			6,40	
Energy efficiency class in cooling			A++	
Annual electricity consumption in cooling **		[KWh/a]	284	
Design load in cooling mode (P design)		[KW]	5,2	
SCOP (average season)			4,00	
Energy efficiency class in heating (average season)			A+	
Annual electricity consumption in heating (average season) **		[KWh/a]	1680	
Design load in heating mode (P design)		[KW]	4,8	
Declared capacity at reference design condition		[KW]	4,4	
(average season)			4,4	
	ity at reference design condition	[KW]	0,4	
(average season)			0,4	
Cooling Capacity at standard rating conditions***		[KW]	5,27	
Heating Capacity at standard rating conditions***		[KW]	5,56	
Power input at standard rating conditions***		[KW]	1,66/1,38	
cooling/heating				
Dimension	Indoor unit	[mm]	990x218x315	
	Outdoor unit	[mm]	810x310x558	
Weight	Indoor unit	[kg]	13,0	
	Outdoor unit	[kg]	37	
Power source			230V~50Hz 1ph	

* Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to [1975]. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be [1975] times higher than 1 kg of CO2, over aperiod of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

** The annual energy consumption kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

*** The standard rating conditions: cooling -outdoor 35°C DB/24°C WB -indoor 27°C DB/19°C WB heating -outdoor 7°C DB/6°C WB -indoor 20°C DB/15°C WB

Operating Range:

	Indoor	Outdoor
Cooling mode	17°C ~ 32°C	-15°C ~ 50°C
Dry mode	10°C ~ 32°C	0°C ~ 50°C
Heating mode	0°C ~ 30°C	-15°C ~ 30°C
Tha maximum humidity:	80%	-

If air conditioner is used outside of the above conditions, certain safety protection features may come into operation and cause the unit to function abnormally or demage.