

Type	Wall Mounted /Heat pump /Multi split		
Model	Indoor unit		3 x FSAMI-Pro-71AE2
	Outdoor unit		FS3MIF-210AE2
Sound power level at standard rating cond. (indoor/outdoor)	[dB(A)]		55/64
Refrigerant type			R410A
Global Warming Potencial (GWP) *			1975
SEER			5,40
Energy efficiency class in cooling			A
Annual electricity consumption in cooling **	[KWh/a]		415
Design load in cooling mode (P design)	[KW]		6,4
SCOP (average season)			4,00
Energy efficiency class in heating (average season)			A+
Annual electricity consumption in heating (average season) **	[KWh/a ]		2136
Design load in heating mode (P design )	[KW]		6,1
Declared capacity at reference design condition (average season)	[KW]		4,910
Back up heating capacity at reference design condition (average season)	[KW]		1,190
Cooling Capacity at standard rating conditions***	[KW]		6,4
Heating Capacity at standard rating conditions***	[KW]		6,74
Power input at standard rating conditions*** cooling/heating	[KW]		2,08/1,75
Dimension	Indoor unit	[mm]	800x275x188
	Outdoor unit	[mm]	845x700x320
Weight	Indoor unit	[kg]	7,3
	Outdoor unit	[kg]	50
Power source			230V~50Hz 1ph

\* Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to [1975]. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be [1975] times higher than 1 kg of CO<sub>2</sub>, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

\*\* The annual energy consumption kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

\*\*\* The standard rating conditions: cooling -outdoor 35°C DB/24°C WB -indoor 27°C DB/19°C WB  
heating -outdoor 7°C DB/6°C WB -indoor 20°C DB/15°C WB

**Operating Range:**

	Indoor	Outdoor
Cooling mode	+17°C ~ +32°C	-15°C ~ 50°C
Dry mode	+10°C ~ +32°C	0°C ~ 50°C
Heating mode	0°C ~ +30°C	-15°C ~ 24°C
The maximum humidity:	80%	-

If air conditioner is used outside of the above conditions, certain safety protection features may come into operation and cause the unit to function abnormally or damage.