

Type	Wall Mounted /Heat pump /Single split		
Model	Indoor unit		FSAI-PM-180BE2
	Outdoor unit		FSOAI-PM-180BE2
Sound power level at standard rating cond. (indoor/outdoor)	[dB(A)]		57/65
Refrigerant type			R410A
Global Warming Potencial (GWP) *			1975
SEER			5,60
Energy efficiency class in cooling			A+
Annual electricity consumption in cooling **	[KWh/a]		330
Design load in cooling mode (P design)	[KW]		5,3
SCOP (average season)			3,80
Energy efficiency class in heating (average season)			A
Annual electricity consumption in heating (average season) **	[KWh/a]		1967
Design load in heating mode (P design)	[KW]		5,3
Declared capacity at reference design condition (average season)	[KW]		4,3
Back up heating capacity at reference design condition (average season)	[KW]		1,0
Cooling Capacity at standard rating conditions***	[KW]		5,275
Heating Capacity at standard rating conditions***	[KW]		5,6
Power input at standard rating conditions*** cooling/heating	[KW]		1,62/1,65
Dimension	Indoor unit	[mm]	945x298x211
	Outdoor unit	[mm]	955x700x396
Weight	Indoor unit	[kg]	12,0
	Outdoor unit	[kg]	48
Power source			230V~50Hz 1ph

* Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to [1975]. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be [1975] times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

** The annual energy consumption kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

*** The standard rating conditions: cooling -outdoor 35°C DB/24°C WB -indoor 27°C DB/19°C WB
heating -outdoor 7°C DB/6°C WB -indoor 20°C DB/15°C WB

Operating Range:

	Indoor	Outdoor
Cooling mode	17°C ~ 32°C	-15°C ~ 43°C
Dry mode	17°C ~ 32°C	-15°C ~ 43°C
Heating mode	max. 27°C	-20°C ~ 24°C
The maximum humidity:	80%	-

If air conditioner is used outside of the above conditions, certain safety protection features may come into operation and cause the unit to function abnormally or damage.